


TRULOK PRELUDE 24 TL

24mm Exposed Suspension System (nominal)


Key Attributes

- **Peakform** patented universal main runner profile for installation either with Prelude TL hook-end cross tees or with Prelude XL stab-end cross tees
- The **Peakform** bulb design increases strength and stability for improved performance
- **Superlock** main runner clip engineered for a strong, secure connection and fast accurate alignment confirmed with an audible click
- Easy to cut thanks to the **Peakform** bulb
- Rotary stitched for additional torsional strength and extra stability during installation
- Slots at 100 mm centres for more flexibility (3600 mm long main runner)
- Prelude TL cross tees with integrally formed hook-on end detail and butt cut joints
- Easy to remove and relocate
- Armstrong Global White

Peakform Main Runner 24 with Superlock Clip




Item Nr.	Dimensions		Content /Carton		Weight/Carton	Carton/Pallet
	length (mm)	height (mm)	pcs	lm	kg	
BP 31 40 32 A*	3600	43	20	72,00	21,00	30
BP 31 43 33 A	3375	43	20	67,50	21,00	30




BP 31 40 32 A*	50	100	33 x 100	100	50
BP 31 43 33 A	337,5	675	2 x 675	675	337,5

Cross Tee Prelude 24 TL




Hook System


BP 11 30 32 C *	1200	35	60	72,00	19,50	72
BP 11 30 31 C	1200	35	60	72,00	15,65	72
BP 11 34 33 C	1800	35	60	108,00	36,65	20
BP 11 36 33 C	1500	35	60	90,00	30,70	20
BP 11 33 33 C	1350	35	60	81,00	24,65	72
BP 11 32 33 C	1000	35	60	60,00	22,55	72



BP 11 30 32 C *	300	2 x 300	300
BP 11 30 31 C	300	2 x 300	300
BP 11 34 33 C	300	4 x 300	300
BP 11 36 33 C	300	3 x 300	300
BP 11 33 33 C	337,5	2 x 337,5	337,5
BP 11 32 33 C	250	2 x 250	250



BP 11 20 32 C *	600	35	60	36,00	9,70	144
BP 11 20 31 C	600	35	60	36,00	7,80	144
BP 11 24 33 C	300	35	120	36,00	11,20	144
BP 11 23 33 C	675	35	60	40,50	13,05	144
BP 11 22 33 C	500	35	60	30,00	9,80	144



All measurements in millimetres

*Colours available : Opal (OL), Carrara (CA), Platinum (PN), Black (BK), Red (RD), Blue (BE), Green (GN), Ivory (IY), Aluminium (AL), Brass (BS), Chrome (CE), Brown (BN), White RAL 9010 (WR).

Cross tee alignment is achieved by locating the tees to the right-hand side of the adjoining section.


TRULOK PRELUDE 24 TL

24mm Exposed Suspension System (nominal)

Physical Data

- Material**
 Double-web galvanised steel
- Surface Finish**
 Baked polyester paint
- Product Family**
 Exposed tee system
- Main Runner/Cross Tee Interface**
 TL butt cut ends
- End Detail**
 Main Runner : bulb-to-bulb connection, staked-on **Superlock** clip, single stitching
 TL Cross Tee : integral hook, single stitching
- Fire Rating**
 Armstrong have an extensive range of grid and tile products which can provide fire and/or structural protection. Please contact Internal Technical Sales Group for the relevant grid and tile combination.

Load Capacity



Maximum Load = 14kg/m²
 (for span (L) deflection limit = L/360)


Test data provided by Stangers Materials Science Laboratories, UK

For other span (L) deflection limits, please multiply the allowable load by the factor indicated:


Span (L) deflection limit	L/300	L/360	L/400	L/500
Multiplier	1.2	1	0.9	0.72

1 BP 31 40 32A 2 BP 11 30 32C 3 BP 11 20 32C


Accessories




BPA 10230 A* Bottom part of nonius hanger



BPA AWDN 20 A* Bent tee bar hanger for threaded rod



BPA 829 B* Suspension hanger for tee bar




BPA 7898 A* Direct ceiling load clip

Accessories (continued)




BPA 819 B Locking hold down clip




BPA 7912 40mm soft fibre panel clip




BPA 7902 18/25mm soft fibre panel clip




BPA 820 B Retaining clip for 15mm tiles (Tegular/MicroLook)



BPA 828 B Retaining clip for 15mm Board panels



BPAC 1430 A* Variable placement Hook End Detail



BPA 7878 A* Exterior hold down clip

All measurements in millimetres

* Suitable for Peakform main runners